



**16A60-9**

## MANUAL RESET FREEZE PROTECTION CONTROL

Designed to Shut Down Cooling Equipment Before Undesirably Low Temperatures are Reached

### FEATURES

- Temperature dial graduated in °F and °C scales.
- Adjustable dial stop to limit minimum setting — Shipped at 36°F (2°C).
- Dustproof steel case with top and bottom knockouts.
- Hydraulic action element — Unaffected by vibration — No leveling required.
- Equipped with special 1/2" packing nut assembly.

### SPECIFICATIONS

Dimensions . . . . . 5<sup>3</sup>/<sub>8</sub>" H x 2<sup>5</sup>/<sub>16</sub>" W x 2<sup>9</sup>/<sub>16</sub>" D  
 Finish . . . . . Grey  
 Thread Size (packing nut) . . . . . 1/2" NPT  
 Agency . . . . . U.L. listed and C.S.A. certified

Model Number	Range	Differential	Capillary Length	Bulb Size	Switch Action	Full Electrical Rating	Motor Rating (Full Load)	
							120 VAC	240 VAC
16A60-9	- 30 to 50°F (- 34 to 10°C)	Manual (3 to 25°C)	10 ft.	5 <sup>3</sup> / <sub>4</sub> " x 3/8"	Open on Fall	HH see page 162	7.4A	3.7A

REFRIGERATION



**16A35-3**

## ICE BANK CONTROL

Controls Compressor to Maintain an Ice Bank of Desired Thickness. Excellent for use on Refrigerated Cabinets Where an Ice Bank is Built as a Means of Storing Refrigeration

### FEATURES

- Specially designed element controls ice bank thickness to within 1/16".
- Thickness of ice determined by location of sensing element to evaporator coil.
- Control stops compressor when ice bank completely covers sensing element and starts compressor when ice bank begins to melt.
- Dustproof steel case with top and bottom knockouts.
- Two mounting straps included.
- Hydraulic action element — No leveling required.

### SPECIFICATIONS

Dimensions . . . . . 5<sup>3</sup>/<sub>8</sub>" H x 2<sup>5</sup>/<sub>16</sub>" W x 2<sup>9</sup>/<sub>16</sub>" D  
 Finish . . . . . Grey  
 Switch Action . . . . . Opens when bulb is covered with ice  
 Agency . . . . . U.L. listed and C.S.A. certified

Model Number	Differential	Capillary Length	Bulb Size	Full Electrical Rating	Motor Rating (Full Load)	
					120 VAC	240 VAC
16A35-3	1/16" ice	7 ft.	5" x 1/2"	FG see page 162	14.0A	7.0A