



**201-8**

**REFRIGERATION TEMPERATURE CONTROLS FOR WALK IN BOXES**

Designed for use in Garages, Factories, Warehouses and Similar Commercial and Industrial Installations

**FEATURES**

- Dust, moisture and vermin resistant heavy metal case.
- Handles inductive and non-inductive loads.
- No leveling required — Mounts in any position.
- Quick response to temperature changes.
- Nickel plated element.

**SPECIFICATIONS**

Dimensions . . . . . 5<sup>3</sup>/<sub>8</sub>" H + 2<sup>1</sup>/<sub>2</sub>" coil x 2<sup>5</sup>/<sub>16</sub>" W x 2<sup>9</sup>/<sub>16</sub>" D  
 Finish . . . . . Grey  
 Agency . . . . . U.L. listed and C.S.A. certified

Model Number	Range	Differential	Switch Action	Full Electrical Rating	Motor Rating (Full Load)		Resistive (Non-Inductive)	
					120 VAC	240 VAC	120 VAC	240 VAC
201-8	20 to 90°F (- 6 to 32°C)	Adj. 3 to 20°F (2 to 11°C)	Close on Rise	FGH See page 416	16.0A	8.0A	25.0A	22.0A
201-20	- 30 to 90°F (- 34 to 32°C)	Adj. 3 to 20°F (2 to 11°C)	Close on Rise	FGH See page 416	16.0A	8.0A	25.0A	22.0A



**1629-33**

**SELECTIVE RANGE TEMPERATURE CONTROL**

Used on Water, Beer and Beverage Coolers, Vegetable and Meat Display Cases and Similar Applications. Special Knob Limits Adjustable Range

**FEATURES**

- Dustproof steel case with top and bottom knockouts.
- Selective range — Allows any 24°F (13°C) section of control temperature range to be used as knob adjusted range.
- Select-range dial labeled 1 through 5.
- High electrical rating allows operation of most equipment without use of relays or motor starter.
- Hydraulic action element with bulb mounting clamp included.

**SPECIFICATIONS**

Dimensions . . . . . 5<sup>3</sup>/<sub>8</sub>" H x 2<sup>5</sup>/<sub>16</sub>" W x 2<sup>9</sup>/<sub>16</sub>" D + <sup>5</sup>/<sub>8</sub>" Knob  
 Finish . . . . . Grey  
 Agency . . . . . U.L. listed and C.S.A. certified

Model Number	Range	Differential	Selective Range	Capillary Length	Bulb Size	Switch Action	Full Electrical Rating	Motor Rating (Full Load)	
								120 VAC	240 VAC
1629-33	- 30 to +90°F (- 34 to +32°C)	Adj. 3.5 to 40°F (2 to 22°C)	24°F (13°C)	8 ft.	5 <sup>1</sup> / <sub>4</sub> " x <sup>3</sup> / <sub>16</sub> "	Close on rise	FGH See page 416	16.0A	8.0A